

When Quick Turnarounds Count

See Reverse for
More Information ▶



TEC® Level Set® 300 Self-Leveling Underlayment



Ideal for quick turnarounds, TEC® Level Set® 300 allows you to quickly smooth substrates without sacrificing performance. This high quality, fiber-reinforced, self-leveling underlayment provides you with a flat, extremely smooth and durable surface that is **walkable in 2-3 hours**. And, you can install moisture-sensitive floor coverings in as little as 16-24 hours.

Contact your local sales rep to request a demo. Have a question? Visit TECQuestions.com.

TECSpecialty.com



@InstallwithTEC



TECInstallationSystems



TECInstallationSystems



TEC Installation Systems


IMAGINE. ACHIEVE.™

Level Set[®] 300 Self-Leveling Underlayment

Ideal for fast track applications, TEC[®] Level Set[®] 300 is a high-performance, fiber-reinforced, calcium aluminate-based, self-leveling underlayment that provides a flat, extremely smooth, and strong, durable surface for finished flooring installation. It is pourable or pumpable for interior applications, offers exceptional workability for an ultra-smooth surface, is walkable in 2-3 hours, can be applied up to 2" (50 mm) neat in single applications and be featheredged to adjoining elevations. For details about TEC[®] product or system warranties, contact your sales associate or visit tecspecialty.com.



Exceptional workability for an ultra-smooth surface



Pourable or pumpable for interior applications



Install moisture sensitive floor covering in 16-24 hours

Features and Benefits

- Formulated for fast-track applications – walkable in 2-3 hours
- Up to 2" (50 mm) neat and can be featheredged to adjoining elevations
- Applied up to 5" (12 cm) with proper aggregate
- High compressive strength - 5,500 psi (38.0 MPa)
- Accepts non-moisture sensitive tile and stone in 4 hours
- Contributes to LEED[®] project points
- Zero VOC

Coverage

Coverages shown are approximate. Actual coverages may vary according to substrate conditions and thickness of applications.

Application Depth	Approximate Coverage per 50 lbs. (22.68 kg)
1/8" (3 mm)	50 sq. ft. (4.65 m ²)
1/4" (6 mm)	25 sq. ft. (2.32 m ²)
1/2" (12 mm)	12.5 sq. ft. (1.16 m ²)
1" (25 mm)	6.25 sq. ft. (0.58 m ²)
2" (50 mm)	3.125 sq. ft. (0.29 m ²)

Packaging

50 lb. moisture-resistant bags (22.68 kg)

Product #7161233111

Suitable Substrates

When properly prepared, suitable substrates include:

- Concrete
- Pavers
- Cement backerboard
- Strip wood flooring
- Exterior grade plywood (with reinforcement mesh)
- Gypsum substrates—minimum tensile bond strength 72 psi (0.5 MPa)
- Ceramic, porcelain or quarry tile
- Cement or epoxy terrazzo
- Metal
- VCT or full glued down, non-cushioned vinyl sheetgoods
- Oriented Strand Board (OSB) (with reinforcement mesh)

Technical Data

Physical Properties

Description	
Physical State	Dry powder
Color	Gray
Working Time	25-35 minutes
Walkable	2-3 hours
Flooring Installation	Tile: 3-4 hours Moisture sensitive: 16-24 hours
Flow (ASTM C1708)	5"-6" (12.7-15.2 cm)
Storage	Store in cool, dry area away from direct sunlight. Do not store open containers.
Shelf Life	Maximum 1 year from date of manufacture in properly stored, unopened package.

Visit tecspecialty.com to learn more