

Up to 3" in One Lift

See Reverse for
More Information ▶

TEC® Level Set® Deep Pour 3 Self-Leveling Underlayment



Discovering deep voids in your substrate shouldn't bring you down. Deep Pour 3 Self-Leveling Underlayment helps you power through your project to quickly fill deep trenches up to 3" in one lift, without aggregate. When dry, Deep Pour 3 gives you a strong, smooth, durable surface that's walkable in three to four hours.

Count on Deep Pour 3 for consistent thick-build applications without compromising return-to-traffic timing.



Level Set[®] Deep Pour 3 Self-Leveling Underlayment

Level Set[®] Deep Pour 3 is ideal for interior thick-build applications. This self-leveling underlayment provides a flat, smooth, durable surface up to 3" (76 mm) in one lift, without aggregate. Pourable or pumpable for interior applications, this calcium aluminate cement-based, self-leveling underlayment is walkable in 3-4 hours. For details about TEC[®] product or system warranties, contact your sales associate or visit tecspecialty.com.

Features and Benefits



Single pour thickness from 3/8" (9 mm) up to 3" (76 mm) neat



Pumpable or pourable



Provides a smooth surface

Additional Features and Benefits

- Walkable in 3-4 hours
- Accepts non-moisture sensitive tile and stone in 4 hours
- Install moisture sensitive floor covering in 36-48 hours
- Contributes to LEED[®] project points

Coverage

Coverages shown are approximate. Actual coverages may vary according to substrate conditions and thickness of applications.

Application Depth	Approximate Coverage per 50 lbs. (22.68 kg)
3/8" (9 mm)	15 sq. ft. (1.39 m ²)
1/2" (12 mm)	11 sq. ft. (1.02 m ²)
1" (25 mm)	5.5 sq. ft. (0.51 m ²)
2" (50 mm)	2.8 sq. ft. (0.26 m ²)
3" (76 mm)	1.8 sq. ft. (0.17 m ²)

Packaging

50 lb. moisture-resistant bags (22.68 kg)

Product #7162083111

Suitable Substrates

When properly prepared, suitable substrates include:

- Concrete
- Ceramic or quarry tile (well-bonded)
- Gypsum substrates-minimum tensile bond strength 72 psi (0.5 MPa)
- Exterior grade plywood or Oriented Strand Board (OSB), with reinforcement mesh

Technical Data

Physical Properties

Description	
Physical State	Dry powder
Color	Gray
Working Time	25-35 minutes
Walkable	3-4 hours
Flooring Installation	Tile: 4 hours Moisture sensitive: 36-48 hours
Flow (ASTM C1708)	5"-6" (12.7-15.2 cm)
Storage	Store away from direct sunlight in a well-ventilated, cool, dry area. If storing after opening, remove all air from container and seal tightly.
Shelf Life	Maximum 1 year from date of manufacture in properly stored, unopened package.

Visit tecspecialty.com to learn more