

# Get Ready to Roll

See Reverse for  
More Information ▶

Breakthrough  
Innovation



## TEC® RollFast™ Vinyl Flooring Adhesive



Installing LVT and LVP can be a pain. TEC® RollFast™ is your solution. This breakthrough innovation eliminates hard-on-the-knees troweling and tedious spraying. RollFast™ allows installers to stand up and easily apply adhesive with a nap roller. It's formulated using installer-friendly technology for easy handling, application, and clean up to reduce fatigue. With moisture resistance up to 95% RH, RollFast™ may eliminate the need for moisture mitigation on newly poured slabs. It resists flooring indentations and disbonding from displacement of adhesive under heavy rolling loads such as hospital beds. Plus, with faster dry time than competing products, RollFast™ allows the installation of LVT, LVP and vinyl sheetgoods\* in 10 to 15 minutes—so your team is ready to rock and roll.

**Turn to TEC® RollFast™ for a roller-applied,  
installer-friendly adhesive for LVT and LVP installations.**



\*Do not use with fiberglass-backed vinyl sheetgoods, nor directly over peel and stick tile.  
Not recommended for use with felt-backed or mineral-backed vinyl sheetgoods, linoleum or rubber.

TEC® RollFast™ Vinyl Flooring Adhesive allows you ease of use, to roll through flooring installations fast and effectively. This breakthrough, user-friendly adhesive is ideal for vinyl tile, vinyl plank and solid vinyl sheetgoods\*. This unique, low odor formulation dries quickly, has excellent resistance to moisture and alkali, provides a long open time and is easy to clean up. For details about TEC® product or system warranties, contact your sales associate or visit [tecspecialty.com](http://tecspecialty.com).



Ideal for LVT, LVP and solid vinyl heterogeneous or homogeneous sheetgoods\*



Roller-applied adhesive allows installer to roll the adhesive onto the substrate efficiently



Fast drying; accepts flooring in 10-15 minutes

\*Do not use with fiberglass-backed vinyl sheetgoods, nor directly over peel and stick tile. Not recommended for use with felt-backed or mineral-backed vinyl sheetgoods, linoleum or rubber.

## Additional Features and Benefits

- Resists flooring indentations and disbonding under heavy rolling loads (hospital beds, furniture, etc.)
- Moisture resistant up to 95% RH / 10 lbs. MVER\*\*
- Extended open time (6-8 hours)
- Heat weld after 60 minutes
- Exceptional coverage at 350-450 ft<sup>2</sup>/US Gallon (35,6-37,2 m<sup>2</sup>/3,78 L) with 1/4" nap roller
- Solvent free and low VOC (VOC <1 g/L)
- LEED® Compliant and CRI Green Label Plus Certified

\*\*Over newly poured concrete, with declining moisture values, and a vapor barrier beneath the slab.

## Packaging

- 4 gallon plastic pail (15.13 L) Product #7188701311
- 1 gallon plastic jug (3.78 L) Product #7188705011

## Coverage

Coverage will vary with the absorption rate (porosity) and surface profile of the substrate. With just one coat of RollFast™ Vinyl Flooring Adhesive, you can lay down the amount of adhesive needed for the specific vinyl flooring being installed. Figures below are presented only as guidelines.

Recommended Roller Size	Approximate Coverage
1/4" Nap	350-450 ft <sup>2</sup> /US Gallon (35,6-37,2 m <sup>2</sup> /3,78 L)
3/8" Nap†	300-350 ft <sup>2</sup> /US Gallon (28-35,6 m <sup>2</sup> /3,78 L)

† For stiff, heavy vinyl flooring a 3/8" Nap Roller may be required (for more information contact Technical Services).

## Suitable Substrates

When properly prepared, suitable substrates include:

- Concrete (all grade levels)
- Underlayment grade plywood
- Gypsum substrates (properly prepared)

## Technical Data

### Physical Properties

Description	
Base	Polymer latex
Physical State	Thin paste
Color	Off white
Open Time	6-8 hours depending on substrate porosity
Weight per Gallon	8.7 lbs/gallon
VOC/Liter of Material	<1 gram (calculated)
Freeze/Thaw Stability	Stable for 3 cycles at 10°F (-12°C)
Storage	For optimal shelf life, store at a moderate room temperature, in closed containers, and protect this adhesive from freezing. If frozen, allow to return to room temperature slowly and stir before use. Avoid prolonged or repeated freeze thaw cycles.
Shelf Life	Maximum 1 year from date of manufacture in unopened package.

For complete details visit [tecspecialty.com](http://tecspecialty.com)