

TEC™

AccuColor®

100% Silicone Sealant

AccuColor 100® sealant is a high performance 100% silicone sealant designed to provide a flexible, long lasting, and water resistant seal. Use for swimming pools, spas, fountains, and other wet area applications.

Showers & Tubs



- Easy to use for fast installation
- Interior/exterior
- Designed to match the most popular TEC® grout colors

Pools & Spas



Fountains



- Permanent flexibility and durability, won't crack or soften
- Excellent weatherability, long life
- Meets ASTM C920 Type S, NS, Class 25



AccuColor®

100% Silicone Sealant

Suitable Substrates

- Natural Stone
- Metals
- Porcelain
- Plastic Surfaces
- Glass
- Ceramic
- Wood
- Masonry

Colors

- 133** Clear
- 902** Ivory
- 903** Birch
- 906** Cornsilk
- 910** Bright White
- 915** Light Smoke
- 927** Light Pewter
- 929** Charcoal Gray
- 931** Standard White
- 933** Standard Gray
- 940** Antique White
- 941** Raven
- 944** Light Chocolate
- 945** Light Buff
- 949** Silverado
- 961** Sandstone Beige
- 969** Coffee
- 982** Summer Wheat
- 984** Almond
- 988** Pearl
- 991** Parchment

Technical Data

Extrusion Rate	200 g/min
Tensile Strength	230 psi (1.57 MPa)
Elongation	350%
Slump	Nil
Shore A Hardness	23
Tack Free Time	20 minutes
Volume Shrinkage	< 3%
Physical State	Soft Paste
Color	20 pigmented colors
Odor	Nil
Open Time [at 72°F (22°C)]	10 minutes
Final Cure	1 day, 14 days for swimming pool applications
Foot Traffic Rating (ASTM C627)	Residential
VOC	31 g/L
Freeze/Thaw Stability	Freeze/thaw stable. If frozen, slowly bring material back to room temperature.
Storage	Store in cool, dry location. Do not store open containers.
Shelf Life	Maximum 1 year from date of manufacture in properly stored, unopened package.



H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451
www.tecspecialty.com